

## 6-way power strips for CONI

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no.	Version		
<b>6-way: 5 x custom modules + power socket outlet</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.004	• 1 socket outlet with earthing contact, child-proof, black, set at 35°		
<b>6-way: 4 x custom modules + power socket outlet</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.005	• 2 socket outlets with earthing contact, child-proof, black, set at 35°		
912.011	• 2 French / UTE socket outlets, child-proof, black, set at 35°		
912.017	• 3 Swiss / CH socket outlets, black, set at 0°		
912.0125*	• 1 UK3.15 A individually fused, child-proof, black, set at 45°		
<b>6-way: 3 x custom modules + power socket outlet</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.006	• 3 socket outlets with earthing contact, child-proof, black, set at 35°		
912.012	• 3 French / UTE socket outlets, child-proof, black, set at 35°		
912.018	• 4 Swiss / CH socket outlets, black, set at 0°		
912.022*	• 3 UK3.15 A individually fused, child-proof, black, set at 90°		
912.0124*	• 2 UK3.15 A individually fused, child-proof, black, set at 45°		
<b>6-way: 2 x custom modules + power socket outlet</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.007	• 4 socket outlets with earthing contact, child-proof, black, set at 35°		
912.013	• 4 French / UTE socket outlets, child-proof, black, set at 35°		
912.019	• 5 Swiss / CH socket outlets, black, set at 0°		
912.035*	• 1 socket outlet with earthing contact, black, set at 35°		
	• 3 Swiss / CH socket outlets, black, set at 0°		
912.0123	• 3 UK3.15 A individually fused, child-proof, black, set at 45°		
<b>6-way: 1 x custom module + power socket outlet</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.008	• 5 socket outlets with earthing contact, child-proof, black, set at 35°		
912.014	• 5 French / UTE socket outlets, child-proof, black, set at 35°		
912.021*	• 4 UK3.15 A individually fused, child-proof, black, set at 90°		
912.0122	• 4 UK3.15 A individually fused, child-proof, black, set at 45°		
<b>6-way: 3 x custom modules + power socket outlet, black and red</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.024	• 1 socket outlet with earthing contact, child-proof, black, set at 35°		
	• 2 socket outlets with earthing contact, child-proof, red, set at 35°		
<b>6-way: 2 x custom modules + power socket outlet, black and red</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.025	• 2 socket outlets with earthing contact, black, set at 35°		
	• 2 socket outlets with earthing contact, red, set at 35°		
<b>6-way: 6 x custom modules</b>		Length: approx. 356 mm	<b>CUSTOM</b>
Anodised aluminium profile; without power connection			
912.001	without socket outlets		
<b>6-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power socket outlets</b>		Length: approx. 356 mm	<b>CUSTOM</b> <b>USB CHARGER</b>
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.0168	• 2 socket outlets with earthing contact, child-proof, black, set at 35°		
	• 1 x USB double charger, 3 x custom modules		
912.0169	• 3 Swiss / CH socket outlets, child-proof, black, set at 90°		
	• 1 x USB double charger, 3 x custom modules		
912.0172	• 2 French / UTE socket outlets, child-proof, black, set at 35°		
	• 1 x USB double charger, 3 x custom modules		
912.0170	• 2 UK3.15 A individually fused, child-proof, black, set at 45°		
	• 1 x USB double charger, 2 x custom modules		