

4-way power strips for Slide / Conference / Top Frame





Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version

CUSTOM | 4-way: 3 x custom modules + power socket outlet | Length: approx. 260 mm

Anodised aluminium profile; power input: GST1813 plug, power output: GST1813 socket







-  909.002 - 1 socket outlet with earthing contact, child-proof, black, set at 35°
-  909.025 - 1 French / UTE socket outlet, child-proof, black, set at 35°
-  909.028* - 1 Swiss / CH socket outlet, black, set at 0°
-  909.065* - 1 Italian / earth contact combination, black, set at 35°

CUSTOM | 4-way: 2 x custom modules + power socket outlets | Length: approx. 260 mm

Anodised aluminium profile; power input: GST1813 plug, power output: GST1813 socket








-  909.003 - 2 socket outlets with earthing contact, child-proof, black, set at 35°
-  909.010 - 2 French / UTE socket outlets, child-proof, black, set at 35°
-  909.017 - 2 Swiss / CH socket outlets, black, set at 0°
-  909.029* - 2 Italian / earth contact combination, black, set at 35°

CUSTOM | 4-way: 1 x custom module + power socket outlets | Length: approx. 260 mm

Anodised aluminium profile; power input: GST1813 plug, power output: GST1813 socket



-  909.004 - 3 socket outlets with earthing contact, child-proof, black, set at 35°
-  909.011 - 3 French / UTE socket outlets, child-proof, black, set at 35°
-  909.018 - 4 Swiss / CH socket outlets, black, set at 0°
-  909.058* - 3 Italian / earth contact combination, black, set at 35°
-  909.0023* - 2 UK 3.15 A individually fused, child-proof, black, set at 45°

CUSTOM | 4-way: 4 x custom modules | Length: approx. 260 mm

Anodised aluminium profile; without power connection





- 909.000 - without socket outlets

USB CHARGER **CUSTOM** | 4-way: 1 x USB double charger (5.2 V / 2.15 A) + custom modules + power socket outlets | L: approx. 260 mm

Anodised aluminium profile; power input: GST1813 plug, power output: GST1813 socket



-  909.0056 - 2 socket outlets with earthing contact, child-proof, black, set at 35°
- 1 x USB double charger, 1 x custom module
-  909.0059 - 2 French / UTE socket outlets, child-proof, black, set at 35°
- 1 x USB double charger, 1 x custom module

8-way power strips for Conference / Top Frame




Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version

USB CHARGER **CUSTOM** | 8-way: 1 x USB double charger (5.2 V / 2.15 A) + custom modules + power socket outlets | L: approx. 444 mm

Anodised aluminium profile; power input: GST1813 plug, power output: GST1813 socket



-  909.0057 - 3 socket outlets with earthing contact, child-proof, black, set at 35°
- 1 x USB double charger, 4 x custom modules
-  909.0060 - 3 French / UTE socket outlets, child-proof, black, set at 35°
- 1 x USB double charger, 4 x custom modules
-  909.0058 - 3 UK 3.15 A individually fused, child-proof, black, set at 45°
- 1 x USB double charger, 2 x custom modules

* No storage type